


A  
Nut




B  
Rubber Gasket



C  
Housing



D  
Sealing



E  
Nut


Thread:PG、PF and NPT.

Material:NYLON 66 (UL 94V-2)

Operating Temperature:-40°C~100°C

Unit:mm


Thread	P/N		Cable Ø	OD(Thread) D	Length (Thread) L	Wrench A / E	Packaging PCS	Remark
	Black	Gray						
PG7	HPG7	HPG7GR	3 ~ 6.5	12.4	8	17 / 15	50	
PG9	HPG9	HPG9GR	4 ~ 8	15.1	8	22 / 19	50	
PG11	HPG11	HPG11GR	5 ~ 10	18.5	8	24 / 22	50	
PG13.5	HPG13.5	HPG13.5GR	6 ~ 12	20.3	9	27 / 24	50	
PG13.5	HPG13.5L	HPG13.5LGR	6 ~ 12	20.3	15	27 / 24	50	
PG16	HPG16	HPG16GR	10 ~ 14	22.3	10	30 / 27	50	
PG21	HPG21	HPG21GR	13 ~ 18	28	11	36 / 33	50	
PG29	HPG29	HPG29GR	18 ~ 25	36.8	11	46 / 42	10	
PG36	HPG36	HPG36GR	22 ~ 32	47	14	59 / 54	10	
PG42	HPG42	HPG42GR	30 ~ 38	53.8	14	65 / 60	10	
PG48	HPG48	HPG48GR	34 ~ 44	58.1	15	70 / 65	10	
PF1/2"	HPF12	HPF12GR	6 ~ 12	20.5	9	27 / 24	50	
NPT3/8"	HPN38	HPN38GR	5 ~ 10	17	15	- /22	50	Without Nut
NPT1/2"	HPN12	HPN12GR	10 ~ 14	21.3	15	- /27	50	
NPT3/4"	HPN34	HPN34GR	13 ~ 18	26.6	15	- /33	50	
NPT1"	HPN11	HPN11GR	18 ~ 25	33.6	15	- /42	10	
NPT1 1/4"	HPN114	HPN114GR	22 ~ 32	42.1	17	- /54	10	



A  
Nut




B  
Rubber Gasket



C  
Housing



D  
Sealing



E  
Nut

Thread:PG、PF and NPT.

Material:NYLON 66 (UL 94V-2)

Operating Temperature:-40°C~100°C

Unit:mm

Thread	P/N		Cable Ø	OD(Thread) D	Length (Thread) L	Wrench A / E	Packaging PCS	Remark
	Black	Gray						
M12 x 1.5	HPM12	HPM12GR	3 ~ 6.5	11.8	15	17 / 15	50	
M12 x 1.5	HPM12S	HPM12SGR	3 ~ 6.5	11.8	8	17 / 15	50	
M16 x 1.5	HPM16	HPM16GR	5 ~ 10	15.8	15	22 / 22	50	
M16 x 1.5	HPM16S	HPM16SGR	5 ~ 10	15.8	8	22 / 22	50	
M20 x 1.5	HPM20	HPM20GR	10 ~ 14	19.8	15	27 / 27	50	
M25 x 1.5	HPM25	HPM25GR	13 ~ 18	24.8	15	33 / 33	50	
M32 x 1.5	HPM32	HPM32GR	18 ~ 25	31.8	15	42 / 42	10	
M40 x 1.5	HPM40	HPM40GR	22 ~ 32	39.9	18	50 / 54	10	
M50 x 1.5	HPM50	HPM50GR	30 ~ 38	49.9	18	59 / 60	10	
M63 x 1.5	HPM63	HPM63GR	34 ~ 44	62.9	18	70 / 65	10	